

2MP Solar Camera(4G + Wi-Fi)



Product Overview

Model No E1IENL41S4

Type 2MP Solar Camera

Key Features

- 1/2'' 2MP Starlight CMOS Sensor
- Day Night Auto (ICR)
- 8 mm Fixed Lens
- Night Visibility 100 Meter
- Built-in 16GB TF Card (Support 128GB Max)
- Supports 4G, Wifi
- Efficient Thin-Film Solar Panels
- 40hrs Battery Backup
- 24AH Lithium Battery
- Onvif

Specification

System	System Security	Supports three-level account, password, user authority management.
	OS	Embedded Linux OS
	P2P(Free)	No need to preset camera, Offer free P2P, Plug & play, Support QR code scanning to view
	Onvif Protocol	Support ONVIF protocol
	PC Browser	Support 13 language remote surveillance, record, alarm, wifi setting etc.
	PC client	Support remote multi-devices monitor, record, alarm etc.
	Cell Phone View	Self R&D APP, Support iPhone, Android smart Phone
	TF Card Record	Built in 16G TF Card, support max 128G
Lens	Lens type	Lens Standard : 8 mm
	IR-CUT	Built-in IR CUT, No color cast
Solar Power	Material	Efficient thin-film solar panels
	Battery	The camera can work for 40 hours when it is with the full batteries
Video	Image Compression	H.264 Main profile/Baseline profile
	Sensor	1/2 2MP Starlight CMOS Sensor
	Video Parameters	Brightness, Contrast, Saturation, Exposure, sharpness can be adjusted
	Image Frame Rate	50Hz:25fps/60Hz:30fps (1920x1080)
Stream	First Stream:	1080P-(1920x1080) 、 (640x352)
	Second Stream:	VGA-(640x352) 、 (320x176)
Night Vision	Night Visibility	100 Meters
	Lux	0.0001LUX(Starlight Level)
Alarm	Motion Detect	Support 4 Independent detection areas(Sensitivity can be adjust 1-100)
	Alarm Action	Support Email Photo Alert, Snapshot and Record saved to TF Card
SIM	TD-SCDMA	Support 4G(B38/B39/B40/B41),3G (B34/B39),2G(900/1800MHZ)
	WCDMA	Support 4G(B1/B3/B5),3G(B1),2G(900/1800MHZ)
	CDMA2000	Support 4G(B1/B3/B5)
WIFI	Wifi	WIFI,802.11 b/g/n
	WIFI Frequency	2400~2483.5MHZ
	WIFI Security	WEP, WPA-PSK,WPA2-PSK,WPA-WPA2 mixed
	WIFI Users	Max support 9 users
Network	Ethernet Interface	One 10/100Mbps RJ-45
	Supported Protocol	TCP/IP, HTTP, TCP, ICMP, UDP, ARP, IGMP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPNP, RTSP etc
	Access Protocol	Support Onvif protocol
	Online Visitor	Support Max 6 visitors at the same time (First Stream:3 visitors;Second Stream:3 visitors)
	IP Mode	Dynamic IP address, static IP address, PPPOE
	Supported OS	Microsoft Win98 SE/ME/2000/XP/Win7/Win8/ Mac OS.
	Browser	IE6.0, IE7.0, IE8.0, FireFox, Google or other standard browser
	AP Function	Support AP connect WIFI
Others	OSD	Support the OSD name, date and time info superposition (On/Off)
	Product Type	Metal Bullet, Outdoor waterproof
	Power	DC5V/2A
	Solar Power	Support Solar Power and Battery (24AH)
	Battery Material	Lithium
	Battery Capacity	2x12AH
	Working Temperature	-10~70℃
	Working Humidity	95% RH
	Size	Item: 370*286*96 mm (LxWxH); Packaging:430x330x130mm(LxWxH)
	Accessories	Adaptor, Antenna*3, CD (including User manual), Bracket, Screw

