

1.3MP IP Bullet Camera, 6mm, Metal Vandal Proof



Product Overview

Model No E1IB1K2311

Type 1.3MP IP Bullet Camera

Key Features

- 1.3 Megapixel High Definition resolution
- 1/3" Sony Progressive CMOS Sensor
- Day Night Auto (ICR)
- 6 mm Fixed Lens
- 30 IR LEDs up to 25 Meter IR Distance
- Metal Vandal Proof
- Ingress Protection IP66 Water Resistant

Specification

Camera	Image Sensor	1/3" Sony Progressive CMOS
	Resolution	960P
	Effective Pixel	1280(H)*960(V)
	TV System	PAL/NTSC
	Electronic Shutter Time	Auto: PAL 1/1-1/10000sec; NTSC1/1-1/10000sec.
	Sync System	Internal
	Usable Illuminations	.01lux
	S/N Ratio	≥252db
	Scanning System	Progressive
	Video Output	Network
Lens	Focus Length	6mm
	Focus Control	Fixed
	Lens Type	Fixed
Night Vision	Infrared LED	30 pcs
	Infrared Distance	25m
	IR Status	Under 10Lux by CDS
	IR Power On	CDS Auto Control
Network	Ethernet	RJ-45 (10/100 Base -T)
	Protocol	IPv4, HTTP, TCP/IP,FTP,NTP, RSTP, UDP, SMTP, DNS, DDNS
	ONVIF	Support
	P2P	Yes, Support QR Code
	POE	Optional, Support IEEE 802.3af
	Wi-Fi	N/A
	Video Delay	0.35 (within the lan)
	Main Stream	1280*960@25fps
	Sub Stream	704*576@25fps, 352*288@25fps
	IE Browser	IE6—11
Camera Features	Day/Night	Color / B&W (IR Cut)
	Compression	H.264/JPEG, Support Record AVI Format
	Image Config.	Saturation, Brightness, Contrast, Sharpness, Mirror, 3D NR, White Balance, BLC, FLK (Flicker Control)
	Motion Detection	Support
	Privacy Masking	3 Rectangular Zone
	BLC	Support
	Recording Mode	NVR/NAS/CMS/Web
General	Housing	Vandal proof (Metal)
	Anti-Cut Bracket	Yes, 3-Axis
	IR Cut Filter	Yes
	Operation Temperature	-10°C ~ + 50°C RH 95% Max
	Storage Temperature	-20°C ~ + 60°C RH 95% Max
	Power Source	DC12V±10%, 700mA
	Dimension	142(W) * 65 (H) * 63(D) mm
	Weight	500g