

## 32 channel 5 in 1 XVR 1080N With 8 SATA



### Product Overview

**Model No** E1B8032N25

**Type** Digital Video Recorder

### Key Features

- **H.264 Video Compression format**
- **GUI OSD interface, user-friendly**
- **32 Channel 5 in 1 XVR ( AHD / TVI / CVI / Analog / IP )**
  - **DVR Mode - 32Ch\*1080N ( AHD )**
  - **HVR Mode - 8Ch\*1080N(AHD) + 8Ch\*1.3MP IP**
  - **NVR Mode - 8Ch\*5MP/16Ch\*3MP / 32Ch\*2MP IP**
- **Support Motion Detection, Video loss, Video blind & Email alerts**
- **Support PTZ RS485 & Alarm RS232**
- **Support 3rd Party ONVIF**
- **16 Channel Audio in , 1 Channel Audio out**
- **8 SATA Port support up to 6 TB**
- **VGA & HDMI Full HD Output**
- **2 USB Port**

### Specification

System	Video Compression Format	H.264
	Video System	PAL / NTSC
	Operation System	Embedded Linux
Video	Video Input	32 CH BNC
	Video Output	1 x VGA & 1 x HDMI Full HD output DVR : 32Ch * 1080N ( AHD / TVI / CVI / Analog ) + 16Ch Playback
	Channel Type (Digital Menu)	HVR : 8Ch * 1080N ( AHD ) + 8Ch * 1.3MP ( IPC ) + 8Ch Playback NVR : 8Ch * 5MP + 4Ch Playback / 16Ch * 3 MP + 8Ch Playback / 32Ch * 2MP + 8Ch Playback
Audio	Audio Input	16 CH RCA
	Audio Output	1 CH RCA
	Audio compression	G.711A
	Bidirectional talk	Yes
Record & playback	Record mode	Manual / Alarm / Motion Detection / Continuous
	Playback Channel	32CH 1080N Real time
	Search Mode	Time / Date / Alarm / Motion Detection
	Playback mode	Normal Play / Fast Forward / Fast Rewind
Storage & backup	HDD Interface	8 x SATA Fixed HDD
	Storage Type	SATA HDD, CMS, Browser
	Capability	SATA HDD up to 6TB each
	Backup Mode	Flash USB / Network
	Backup format	H.264/AVI
PTZ	PTZ	1 x RS485
	Protocol	PELCO-P, PELCO-D, HY, NEON, PANASONIC, SAMSUNG, PHILIPS, SANLI, SANTACHI, SHARP, SONY, YAAN
Alarm	RS232	1 x RS232 with 15 alarms
	Motion Detection	Support
	Video loss	Support
	Video Blind	Support
	Email alerts	Support
Network	Network interface	RJ45 10M/100M self-adaption
	Protocol	TCP/IP, DHCP, DDNS, DNS, PPPoE, UPNP, NTP, SMTP
	USB	2* USB 2.0 ports
	Compatibility Browser	Internet Explorer (IE 6-11)
	IPC Protocol	Support ONVIF
	Simultaneous Remote Viewer	4 User Online
	Mobile View	Android, iPhone
General	Power supply	ATX110-220V 300W 50-60Hz
	Power Consumption	<18W (without HDD)
	Working environment	Temperature:0℃—+55℃ , Humidity:10%—90% ,