


## 2MP IP Dome Camera



### Product Overview

**Model No** E1ID1M13N1-S

**Type** Dome Camera

### Key Features

- **2.0MP HD resolution clear and fine images**
- **Support multiple intelligent analysis**
- **Support 2D/3D noise reduction, digital wide dynamic range, BLC**
- **Advanced H.265/H.264 video compression, Super low rate, high definition quality of image**
- **ONVIF**
- **2.8/4/6mm Fixed Lens**
- **External PoE included**
- **24 pcs IR LEDs up to 30Meter IR Distance**
- **Support various mobile monitoring (iOS, Android)**
- **Metal Vandal Proof**
- **Ingress Protection IP67 Water Resistant**

### Specification

Camera	Image Sensor	1/2.7" FHD Resolution CMOS Sensor
	Resolution	2MP
	Electronic Shutter Time	1/3 to 1/100,000
	Slow Shutter	Yes
	S/N Ratio	≥52db
	Min. Illumination	color 0.1Lux@F1.2,black/white 0.01Lux@F1.2
	Video Output	Network
Camera Features	Day/Night	Support IR-CUT
	Video Compression	H.265 / H.265+ / H.264 / H.264+ support dual stream, AVI
	Noise reduction	Support 2D/3D
	WDR	Support (0 - 100) D-WDR
	Image Config.	BLC, FLK (Flicker Control), AGC, AES, Defogging, Mirror, Flip, Anti flicker, IR Swap
	Record mode	NVR/CMS/Web
Encode	Main Stream	2MP(1920*1080)@25fps, 1MP (1280*720)@25fps
	Sub Stream	25fps@D1, 25fps@CIF
	Video Bitrates	VBR/CBR (32Kbps~8Mpbs variable)
Lens	Focus Length	2.8/4/6mm
	Infrared LED	24 pcs
	Infrared Distance	30m
	IR Power On	Auto Day & Night
Alarm Trigger	Alarm	Motion detection video tampering network disconnected IP address conflict, illegal login, HDD error, HDD full.
Audio		1 Input & 1Output , (With Environment Noise Filtering)
IVA	Intelligence analysis	Alarm line, Alarm region, Goods stranded
Network	Ethernet	1*RJ45 10/100M adaptive Ethernet port
	Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP,UPnP", SMTP, SNMP, IGMP, 802.1X, Qos, IPv6, Bonjour.
	Storage	Support built-in microSD/SDHC/SDXC card (128G), local storage and NAS (NFS, SMB/CFSL and 1 GMP 802.1x Qus IPv6 UDP Bonjour
	ONVIF	Support
	P2P	Support
	POE	External POE Included
General	2-Axis Adjustment	Pan:0 to 355 , Tilt:0 to 70
	Simultaneous Live view	Up to 6Channels
	View	Up to 32 Users
	Power Source	DC12V±10%, Max ≤ 4W
	Operation Humidity	-30°C ~ + 90°C RH
	Storage Temperature	-20°C ~ + 60°C
	Weather proof	IP67
	Housing	Metal vandal proof