

650TVL 22X Analog Outdoor PTZ Camera



Product Overview

Model No E2AP1B732N

Type 650TVL 22X Analog Outdoor PTZ Camera

Key Features

- 1/3" Super HAD II SONY Effio Sensor
- 650TVL resolution
- 6PCS Array LED upto 100Mtr distance
- 3.9 - 85.5mm Varifocal Lens
- 22X Optical zoom
- Pan rotation - 360°
- Tilt rotation - 93°
- Waterproof - IP66
- Auto Temperature Control

Specification

Camera	Image Sensor	1/3" Super HAD II Sony CCD, Effio
	Horizontal Resolution	650TVL
	S/N Ratio	>55db
PTZ	Horizontal Rotation	200°/s
	Tilt Rotation Speed	100°/s
	Horizontal Rotation	360°
	Tilt Rotation Range	93°
	Auto Flip	Horizontal: 180°, Vertical: 90°
	A-B Scan	User Programmable
	A-B Scan Speed	1-9 Speed Setting Available
	360° Scan Speed	1-9 Speed Setting Available
	Dwell Preset	5-60 Interval
	Preset Points	220
	Go to Preset Speed	200°/s
	Guard Tour	3 Groups
	Guard Points	Max. 16 Points, dwell time user selectable
	Pattern Scan	4 pcs
	Pattern Scan Record	Max. 15 minutes, Max. 512 Commands
	Park Action	Home Position, 360° Scan/ A-B Scan/ Guard tour 1-3
	Home POS Time	1-60 minutes available
PWR on Action	Memory as power off / 360°Scan/ A-B Scan/ Preset Cruise 1-	
Auxiliary	Communication Protocol	Pleco-D, Pleco-P
	Communication	RS485 Bus
	Baud Rate	1200 / 2400 / 4800 / 9600 bps
General	Operating Temperature	Outdoor: -40° ~ +60°
	Operating Humidity	≤95% Non Condensing
	Heater & Blower	Auto Temperature Control
	Auto Control IR LED	PWM
	OSD Menu	English
	IR Illumination Distance	SDM
	Power	DC 12V ≤4A
	Consumption	≤20W
	Lightning Protection	Transient Voltage 6000V
	Dimension	28*32*20 (cm)
Weight	3.4Kgs	