

## 4 channel 5 in 1 XVR - 1080N With 2 SATA



### Product Overview

**Model No** E1B2004N26

**Type** Digital Video Recorder

### Key Features

- **H.264 Video Compression format**
- **GUI OSD interface, user-friendly**
- **4 Channel Tribrid DVR ( AHD / TVI / CVI / IP / Analog )**
  - **DVR Mode - 4\*1080N(AHD/TVI/CVI/XVI/Analog)**
  - **HVR Mode - 2\*720P(AHD) + 2\*1MP (IPC)**
  - **NVR Mode - 8\*2MP/12\*1.3MP**
- **Support Motion Detection, Video loss, Video blind & Email alerts**
- **Support 4 CH playback simultaneously**
- **Support 3rd Party ONVIF**
- **4 Channel Audio in , 1 Channel Audio out**
- **2 SATA Port support up to 6 TB**
- **VGA & HDMI Full HD Output**
- **3 USB Port**

### Specification

System	Video Compression Format	H.264
	Video System	PAL / NTSC
	Operation System	Embedded Linux
Video	Video Input	4CH BNC
	Video Output	1 x VGA & 1 x HDMI Full HD output
	Channel Type (Digital Menu)	DVR : 4*1080N ( AHD / TVI / CVI / Analog ) + 4 Playback HVR : 2*720P ( AHD ) + 2*1MP ( IPC ) NVR : 8*2MP + 2 Playback / 12*1.3 + 4 Playback
Audio	Audio Input	4 CH RCA
	Audio Output	1 CH RCA
	Audio compression	G.711A
	Bidirectional talk	Yes
Record & playback	Record mode	Manual / Alarm / Motion Detection / Continuous
	Playback Channel	4CH 1080N Real time
	Search Mode	Time / Date / Alarm / Motion Detection
	Playback mode	Normal Play / Fast Forward / Fast Rewind
Storage & backup	HDD Interface	2 x SATA Fixed HDD
	Storage Type	SATA HDD, CMS, Browser
	Capability	SATA HDD up to 6TB each
	Backup Mode	Flash USB / Network
	Backup format	H.264
PTZ	PTZ	1 x RS485
	Protocol	PELCO-P, PELCO-D, HY, NEON, PANASONIC, SAMSUNG, PHILIPS, SANLI, SANTACHI, SHARP, SONY, YAAN
Alarm	Motion Detection	Support
	Video loss	Support
	Video Blind	Support
	Email alerts	Support
Network	Network interface	RJ45 10M/100M self-adaption
	Protocol	TCP/IP, DHCP, DDNS, DNS, PPPoE, UPNP, NTP, SMTP
	USB	3* USB 2.0 ports
	Compatibility Browser	Internet Explorer (IE 6-11)
	IPC Protocol	Support ONVIF
	Simultaneous Remote Viewer	4 User Online
	Mobile View	Android, iPhone
General	Power supply	12V/4A
	Power Consumption	<15W (without HDD)
	Working environment	Temperature: -10% - +50% , Humidity:10%—90% ,

