


16 Channel 5 in 1 XVR - 1080N, 1 SATA



Product Overview

Model No E1X1016N26

Type 16 Channel 5 in 1 XVR - 1080N

Key Features

- **H.264 Video Compression**
- **8CH 5 IN 1 XVR (Analog, AHD, TVI, CVI & IP)**
 - **DVR: 16CH 1080N AHD/TVI/CVI/Analog**
 - **HVR: 8CH 1080P (AHD /TVI/CVI/Analog) + 8CH 960P IP**
 - **NVR: 8CH 1080P IP + 8CH 960P IP, 4CH*5MP IP**
- **Support 3rd Party ONVIF IP Camera**
- **Support D-WDR, BLC, AGC**
- **Support Motion Detection, Video Loss, Video Blind, Abnormality (No storage, Storage error, Storage no space)**
- **1 CH Audio in & 1 CH Audio out**
- **1 SATA Port support up to 6TB HDD**
- **Full HD HDMI and VGA Output**
- **RS485 support**
- **2*USB 2.0 Ports**
- **Support P2P Cloud (Android / iOS)**

Specification

Video	Codec	H.264 Video Compression
	Encode	16*1080N@12fps
	Decode	8*1080N@12fps
	Multi-mode	AHD:16CH*1080N@12fps + 16CH Playback HVR: 8CH*1080P(AHD)+8CH*1080P(IP)@25fps + 8CH Playback NVR:8CH 1080P IP + 8CH 960P IP+ 8CH Playback, 4CH*5MP IP@15fps + 2CH Playback
Display	Display window	16/9/8/4 view
	Resolution	1920*1080, 1440*900, 1280*1024, 1280*720, 1024*768
Audio	Compression	G.711a
	Audio in & Out	1CH Input & 1CH Output
Record & Backup	Record mode	Schedule/Manual/Stop
	Playback mode	Regular/ Detect / Alarm
	Storage Mode	HDD Storage, Network Storage
	Backup	Support Flash disc, Network, P2P backup
Interface	Video input	16CH*BNC, 8CH*2MP IPC+8CH*1.3MP IPC, 4CH*5MP IPC
	HDMI output	1CH*HDMI FULL HD Output
	VGA output	1CH*VGA Full HD Output
	Audio I/O	1CH Input / 1CH Output
	Ethernet port	1CH*10/100Mbps Ethernet RJ45 port
	RS485	Support for Analog PTZ Communication
	USB port	2*USB2.0 ports
	HDD	1*SATA interface (Up to 6TB)
General	Temperature	-10° - + 60°
	Humidity	10% - 90% RH
	Power supply	12V/2A
	Consumption	<10W (Without HDD)