

2MP AHD PTZ Dome 30X



Product Overview

Model No E2BP2L83N4

Type High Speed Dome Camera

Key Features

- Support TVI, CVI, AHD, CVBS signal output, maximum support 1920 × 1080 @ 30fp HD screen output
- Support coaxial visual control function
- Support 10 times optical zoom
- Efficient infrared array, low power consumption, irradiation distance of 80m
- Support 3D digital noise reduction, electronic image stabilization, auto iris, auto focus and other functions
- Supports automatic recognition of Pelco-P / D protocol under RS-485 control
- Support the level of 60 ° / S rotation, vertical 45 ° / S
- Support OSD menu operation and prompt function
- Support power-off memory function
- Support high-definition video / control signal coaxial transmission, normal 753-type coaxial cable at 1080P @ 25 / 30fps resolution Lossless transmission distance up to 500 meters
- Lightning, surge, surge, IP66 protection

Specification

parameter	Parameter value		
Movement	Image Sensor	1/3 "2 million Sony 323 progressive scan CMOS	
	Maximum image size	1920 * 1080	
	Magnification	10 times optical zoom	
	3D noise reduction	stand by	
	Gain control	automatic / manual	
	BLC	stand by	
	Day and night mode	Automatic ICR filter color to black	
	Signal to noise ratio	≥50dB	
	White balance	Automatic, indoor, outdoor, sodium lamp mode, manual	
	Minimum illumination	0.1Lux (color mode); 0.01Lux (black and white mode) 0 Lux (infrared light on)	
Lens	Focus mode	Automatic / semi-automatic / manual	
	focal length	5.1mm-51mm	
	Aperture value	F1.6 ~ F3.0	
	Field of view	4.64 ° ~ 49 °	
Features	Horizontal rotation range	360 °	
	Vertical rotation range	93 °	
	Horizontal rotation speed	60 ° / s	
	Vertical rotation speed	45 ° / s	
	The number of prefabricated positions	220	
	Tour group number	3 groups (16 points independently edit stay and stay, cruise speed, synchronously support PAT-TERN)	
	Caretaker mode	360 scan / two point scan / preset tour /	
	Preset dwell time	1 ~ 60 seconds (editable)	
	The maximum transmission distance	Ordinary 75-3 coaxial cable transmission over 500 meters	
	Video standard	AHD / TVI / CVI / CVBS	
	Output frame rate	1280H x 720V / 25fps / 1280H x 720V / 30fps	
		1920H x 1080V / 25fps / 1920H x 1080V / 30fps	
	Infrared light	Using 6 high-power dot matrix infrared light	
	powered by	DC12V / 3A power supply	
	Power consumption	<15W	
	Dynamic Range	83.5dB	
	temperature control	Program control, automatic thermostat	
working environment	Indoor (0°C ~ + 40°C) Outdoor (-40 ™ ~ + 60 ™)		
weight	2.8KG (net weight), 3.3KG (gross weight)		



+91 9108951246



sales@envision.in



+91 9590829578, support.cctv@envision.in

